

CRAIG OCEAN SYSTEMS, INC.
Catalog & pricing for the MCU500 and components

ITEM

PART NUMBER

TOTAL LIGHT MEASUREMENTS:



EXTECH 401025 Light Meter. Foot Candle or LUX measurements. Accurate measurement of light intensity over a 0-50,000 LUX range. May be used with ND filters to extend the range. When used with the MCU, it provides integrated light readings, in LUX-Hours, as well as simple LUX readings. 098-EX-401025

Use with the COS model 30050 EXTECH interface signal conditioner module (provides both signal conditioning and amplification of the 200mV output to a 0-5 volt output, and eliminates the need for the 9 volt battery).

PRESSURE SENSORS:



Model PDA005, 0-5 psi, 0-10 VDC output with span and zero adjustments. Designed for direct interface to the MCU500. Excellent for monitoring air or gas pressure. 0.125 inch tubing press-on fitting. 200-40400

Model PDA015, 0-15 psi, 0-10 VDC output with span and zero adjustments. 0.125 tubing press-on fitting. 200-40402

Model PDA030, 0-30 psi, 0-10 VDC output with span and zero adjustments. 0.125 tubing press-on fitting. 200-40405

Model 40310, Barometric pressure sensor, span and zero adjustable through the range of 27.800 through 31.200 InHg. 0-5 VDC output. 200-40310